

Appendiks B-I: PC-software kildekode

```
1  using System;
2  using System.Drawing;
3  using System.IO.Ports;
4  using System.Text;
5  using System.Windows.Forms;
6  using MySql.Data.MySqlClient;
7  using ZedGraph;
8
9  namespace CDH_Controller
10 {
11     public partial class Form1 : Form
12     {
13         SerialPortController m_comPort = new SerialPortController(115200);
14         string m_portStr = "COM4";
15         StringBuilder str = new StringBuilder();
16         MySqlConnection conDatabase; // The "global" instance of MySqlConnection
17         int currScore;
18         int game = 0;
19
20         #region Form1 events
21
22         public Form1()
23         {
24             InitializeComponent();
25         }
26
27         private void Form1_Load(object sender, EventArgs e)
28         {
29             lbData.Items.Add("Opening connections...");
30
31             OpenCom();
32
33             OpenSql();
34
35             lbData.Items.Add("Done initializing. Check above for errors.");
36             lbData.Items.Add("-----");
37
38             RefreshPlayers();
39
40             InitGraph(zgGraph);
41             SetSize();
42         }
43     }
```

Appendiks B-I: PC-software kildekode

```
44 private void Form1_FormClosed(object sender, FormClosedEventArgs e)
45 {
46     try
47     {
48         conDatabase.Close();
49         m_comPort.CloseConnection();
50     }
51     catch { }
52 }
53
54 private void Form1_Resize(object sender, EventArgs e)
55 {
56     SetSize();
57 }
58
59 #endregion
60
61 #region Connections
62
63 /// <summary>
64 /// Opens the COM port
65 /// </summary>
66 private void OpenCom()
67 {
68     try
69     {
70         // Open the connection, using the global SerialPortController, m_comPort
71         m_comPort.OpenConnection(m_portStr, new System.IO.Ports.SerialDataReceivedEventHandler(port_DataReceived));
72
73         // Add a message to the log
74         lbData.Items.Add(string.Format("{0} has been opened", m_portStr));
75
76         // Enable buttons that should only be used if the COM port has been opened
77         btnSend.Enabled = true;
78         btnGame.Enabled = true;
79     }
80     catch // If an error occurs, show a message in the log
81     {
82         lbData.Items.Add(string.Format("Connecting to {0} failed!", m_portStr));
83     }
84 }
85
86 /// <summary>
```

```

87  /// Connects to the MySQL server
88  /// </summary>
89  private void OpenSql()
90  {
91      try // try-catch makes sure the program doesn't crash in case connecting failed
92      {
93          // Initialize the instance of the MySqlConnection class.
94          conDatabase = new MySqlConnection("server=localhost;" + "database=test;" + "uid=root;");
95          // Open the connection
96          conDatabase.Open();
97          // In case all goes well, add a message to the log
98          lbData.Items.Add("SQL connection established");
99          // ..and enable btnAddPlayer, allowing the user to add players to the database
100         btnAddPlayer.Enabled = true;
101     }
102     catch (Exception ex)
103     {
104         // If something went wrong while trying to connect, show the error message in the log
105         lbData.Items.Add(string.Format("SQL connection failed: {0}", ex.Message));
106     }
107 }
108
109 private void cbCOM_SelectedIndexChanged(object sender, EventArgs e)
110 {
111     m_portStr = cbCOM.Text;
112 }
113
114 private void btnReconnectCOM_Click(object sender, EventArgs e)
115 {
116     OpenCom();
117 }
118
119 private void btnReconnectSQL_Click(object sender, EventArgs e)
120 {
121     OpenSql();
122 }
123
124 #endregion
125
126 #region Score & game management
127
128 /// <summary>
129 /// When clicked, a "switch game"-command is sent to the master

```

```

130  /// </summary>
131  private void btnGame_Click(object sender, EventArgs e)
132  {
133      // The global variable game is set to the selected game in cbGame.
134      // The index of cbGame starts from 0, so add 1
135      game = cbGame.SelectedIndex + 1;
136      string gameStr;
137
138      // If games with no. > 99 should be supported, a change in the master-software should be made
139      if (game > 99)
140          throw new Exception("Games with no. > 99 is currently not supported!!");
141
142      // If the game no. is < 10, add a leading 0
143      if (game < 10)
144          gameStr = string.Format("G0{0}", game);
145      else
146          gameStr = string.Format("G{0}", game);
147
148      // Send the command
149      m_comPort.SendString(gameStr);
150      addToLb(string.Format("Sent: {0}", gameStr));
151  }
152
153  /// <summary>
154  /// Fetches the Id of a player
155  /// </summary>
156  /// <param name="name">The name of the player</param>
157  /// <returns>The Id of the player</returns>
158  private int getPlayerId(string name)
159  {
160      try
161      {
162          // Create an instance of the MySqlCommand class
163          MySqlCommand cmd = conDatabase.CreateCommand();
164          // Build the sql command
165          cmd.CommandText = string.Format("SELECT Id FROM players WHERE Name='{0}'", name);
166          // Create an instance of the MySqlDataReader class
167          MySqlDataReader rdr = cmd.ExecuteReader();
168          // Read the first row and save the result in the int id
169          rdr.Read();
170          int id = rdr.GetInt32(0);
171          // Close the reader and return the id
172          rdr.Close();

```

```

173         return id;
174     }
175     catch
176     {
177         // In case something goes wrong, return a 0
178         return 0;
179     }
180 }
181
182 /// <summary>
183 /// Saves the score of a person playing a game
184 /// NOTE: Uses the global variable "game"
185 /// </summary>
186 /// <param name="score">The score</param>
187 /// <param name="name">The name of the player</param>
188 private void SaveScore(int score, string name)
189 {
190     // If the connection is opened...
191     if (conDatabase.State == System.Data.ConnectionState.Open)
192     {
193         // Assemble the SQL-command
194         // string.format combines a string with a number of substrings
195         MySqlCommand cmd = new MySqlCommand(
196             string.Format("INSERT INTO scores (Score, PlayerId, GameId) VALUES ({0}, {1}, {2})", score,
197 getPlayerId(lbPlayers.SelectedItem.ToString()), game),
198             conDatabase);
199         // Execute the command, inserting the score
200         cmd.ExecuteNonQuery();
201     }
202 }
203
204 #endregion
205
206 #region Graphing
207
208 /// <summary>
209 /// Collects scores from the database related to the game w/ ID cbGame.SelectedIndex+1 and the player selected in lbPlayers
210 /// </summary>
211 private void btnGraph_Click(object sender, EventArgs e)
212 {
213     // Create a new instance of the PointParList class
214     PointPairList list = new PointPairList();
215

```

```

216         //Create the MySqlCommand and start the DataReader
217         MySqlCommand cmd = conDatabase.CreateCommand();
218         cmd.CommandText = string.Format("SELECT Score FROM scores WHERE PlayerId={0} AND GameId={1} ORDER BY Id",
219 getPlayerId(lbPlayers.SelectedItem.ToString()), cbGame.SelectedIndex+1);
220         MySqlDataReader rdr = cmd.ExecuteReader();
221
222         // While there's still new data to read, add the data to the PointParList
223         int i = 0;
224         while (rdr.Read())
225         {
226             list.Add(i, rdr.GetInt32(0));
227             i++;
228         }
229         rdr.Close();
230
231         // Finally, put the data in the list on the graph
232         AddToGraph(zgGraph, list, string.Format("{0}'s scores", lbPlayers.SelectedItem.ToString()), colorDialog.Color,
233 SymbolType.Diamond);
234     }
235
236     /// <summary>
237     /// Adds a PointParList of data to the zgc graph
238     /// </summary>
239     /// <param name="zgc">The graph to add the data to</param>
240     /// <param name="list">The list of data to add</param>
241     /// <param name="title">The title of the dataset</param>
242     /// <param name="color">The color of the dataset</param>
243     /// <param name="symbol">The symbol used to illustrate the dataset</param>
244     private void AddToGraph(ZedGraphControl zgc, PointPairList list, string title, Color color, SymbolType symbol)
245     {
246         // Create an instance of the GraphPane class, from the graph (zgc)
247         GraphPane myPane = zgc.GraphPane;
248
249         // Add a curve to the graph with the specified title, data, color and symbol
250         LineItem curve = myPane.AddCurve(title, list, color, symbol);
251
252         //curve.Symbol.Fill = new Fill(Color.White);
253         // Fill the background with a slightly golden gradient
254         myPane.Chart.Fill = new Fill(Color.White, Color.LightGoldenrodYellow, 45F);
255
256         // Fill the pane background with a color gradient
257         //myPane.Fill = new Fill(Color.White, Color.FromArgb(220, 220, 255), 45F);
258

```

```

259         // Refresh the graph
260         zgc.AxisChange();
261         zgc.Refresh();
262     }
263
264     /// <summary>
265     /// Init the graph window with default values
266     /// </summary>
267     /// <param name="zgc">The graphwindow to init</param>
268     private void InitGraph(ZedGraphControl zgc)
269     {
270         GraphPane myPane = zgc.GraphPane;
271
272         // Set the titles and axis labels
273         myPane.Title.Text = "Scores";
274         myPane.XAxis.Title.Text = "Spil nr.";
275         myPane.YAxis.Title.Text = "Score";
276     }
277
278     /// <summary>
279     /// Resizes the graphwindow to fit the fom
280     /// </summary>
281     private void SetSize()
282     {
283         zgGraph.Location = new Point(10, 260);
284         // Leave a small margin around the outside of the control
285         zgGraph.Size = new Size(this.ClientRectangle.Width - (30 + lbPlayers.Size.Width), this.ClientRectangle.Height - 270);
286     }
287
288     private void btnSetColor_Click(object sender, EventArgs e)
289     {
290         colorDialog.ShowDialog();
291         btnSetColor.BackColor = colorDialog.Color;
292     }
293
294     private void btnResetGraph_Click(object sender, EventArgs e)
295     {
296         // Goes here
297         zgGraph.GraphPane.CurveList.Clear();
298         zgGraph.Refresh();
299     }
300
301     #endregion

```

```

302
303 #region Serial communication
304 private void addToLb(string str)
305 {
306     Invoke(new MethodInvoker(
307         delegate { lbData.Items.Add(string.Format("{0}", str));
308                     lbData.SelectedIndex = lbData.Items.Count - 1;
309                     lbData.SelectedIndex = -1; }
310     ));
311 }
312
313 /// <summary>
314 /// Triggered when data is received on the COM-port
315 /// </summary>
316 private void port_DataReceived(object sender, SerialDataReceivedEventArgs e)
317 {
318     // Collect the message waiting in the input buffer
319     string inp = m_comPort.port.ReadExisting();
320
321     // The message is appended to the stringBuilder str
322     str.Append(inp);
323
324     // If there's a new line character, the message is complete, and we continue processing
325     // if not, the semi-completed message will wait until the next part of the message is received
326     if (inp.Contains("\n"))
327     {
328         // The message is added to the log
329         addToLb("Received: " + str.ToString());
330
331         // If the message contains "SCORE:", its a score-entry, that should be added to the database
332         if (str.ToString().Contains("SCORE:"))
333         {
334             // Catch the actual score (int), and cut the "SCORE:"-part off
335             currScore = Convert.ToInt32(str.ToString().Split(':')[1]);
336
337             // Save the score to the database
338             SaveScore(currScore, lbPlayers.SelectedItem.ToString());
339         }
340         // If the message contains "STATUS", its a STATUS-request from the master
341         else if (str.ToString().Contains("STATUS"))
342         {
343             // This message means the master is trying to verify the connection - we reply with "OK"
344             m_comPort.SendString("OK\n");

```

```

345
346         // And lets add the data to the log
347         addToLb("Sent: OK");
348         addToLb("-Connection to Master verified-");
349     }
350
351     // Since the message is over and processed, clear the stringBuilder
352     str.Clear();
353 }
354
355 private void btnSend_Click(object sender, EventArgs e)
356 {
357     m_comPort.SendString(tbSend.Text);
358     addToLb(string.Format("Sent: {0}", tbSend.Text));
359     tbSend.Text = "";
360     tbSend.Focus();
361 }
362 #endregion
363
364 #region Player-management
365
366 /// <summary>
367 /// Fetches players from the SQL-server and adds them to lbPlayers
368 /// </summary>
369 private void RefreshPlayers()
370 {
371     try
372     {
373         // Clear lbPlayers, first
374         lbPlayers.Items.Clear();
375         // Initialize and set the command
376         MySqlCommand cmd = conDatabase.CreateCommand();
377         cmd.CommandText = "SELECT Name FROM players ORDER BY Id";
378         // Start the DataReader
379         MySqlDataReader rdr = cmd.ExecuteReader();
380         while (rdr.Read()) // While there's more data to read
381         {
382             // Add the string in column 0 of the current row to lbPlayers
383             lbPlayers.Items.Add(rdr.GetString(0));
384         }
385         // Close the reader
386         rdr.Close();
387     }

```

```

388     }
389     catch { } // If something goes wrong nothing currently happens. Just ignore the error.
390 }
391
392 /// <summary>
393 /// Handles a click on btnAddPlayer
394 /// </summary>
395 private void btnAddPlayer_Click(object sender, EventArgs e)
396 {
397     // If the MySQL-database connection has been opened...
398     if (conDatabase.State == System.Data.ConnectionState.Open)
399     {
400         // Initialize the command to insert players into the database
401         MySqlCommand cmd = new MySqlCommand(
402             string.Format("INSERT INTO players (Name) VALUES ('{0}')" , tbPlayername.Text),
403             conDatabase);
404         // Execute the command, thereby inserting the player
405         cmd.ExecuteNonQuery();
406         // Refresh lbPlayers
407         RefreshPlayers();
408
409         // Empty tbPlayername and get ready for a new entry
410         tbPlayername.Text = "";
411         tbPlayername.Focus();
412     }
413 }
414
415 private void tbPlayername_Enter(object sender, EventArgs e)
416 {
417     tbPlayername.Text = "";
418 }
419
420 private void lbPlayers_SelectedIndexChanged(object sender, EventArgs e)
421 {
422     btnGraph.Enabled = true;
423     labelPlayer.Text = string.Format("Spiller: {0}", lbPlayers.SelectedItem.ToString());
424 }
425
426 #endregion
427 }
428 }
429
430

```